Refresh Lighting & Energy Solutions



LED Slimline LED Flood Light – 1000W

Model: RL-SFL-1000W

LED flood lights are suitable for both outdoor and indoor commercial applications such as parking areas, billboards and common areas.

Product Features

- Quality Driver
- Aluminium die cast housing
- 60° Round Beam Angle
- Full range power input 90~305VAC
- Weight: 33kg
- IP66 Waterproof housing





Options:

Image shown with optional cut-off hood fitted

Lens Options:

Round Beam





SPECIFICATION	
Colour	(5000K)
Lumen (Im)	112,2188lm
Efficiency (Lm/w)	>112lm/w
Light Source	LED
CRI (%)	>80%
Beam Angle	60°
Power Requirement	AC 90~305V
Power Consumption	1000W
Housing	Die Cast Aluminium and Toughened Glass
Lifespan	> 50,000 hours
Operation Temperature	-20°C~+60°C
Dimension (mm)	672 x 1120 x 188mm
Impact Rating	IK08
Protection Rating	IP66
Warranty	5 years

Refresh Lighting & Energy Solutions PTY LTD. 1/13 Commerce Circuit, Yatala QLD 4207 Phone – 1300 911 866 Website – www.refreshlighting.com.au Email – info@refreshlighting.com.au