



- 1. Aluminium Alloy Case.
- 2. Lighting mode uses intelligence radar sensor for long distance.
- 3. 140° view angle, lighting a larger area
- 4. Easy to install, easy maintenance
- 5. Remote control, UVA technology, 30m control operation
- 6. Premium Bridgelux LED chips <100,000 hours
- 7.4 lighting modes
- 8. Adjustable mounting spigot
- 9. Automatic day/night sensor
- 10. User friendly







SPECIFICATION	
Colour	6500K
Lumen (Im) – Full	6800lm
Light Source	LED
Beam Angle	140°
Mounting Height	5-7metres(suggest install 17-23m apart)
Power Consumption	40W
Solar Battery	27AH 12.8V
Charging time	6 hours of bright sunlight
Redundancy	3 ~ 7 Days
Housing	Aluminium + PC
Operation Temperature	-25°C~+65°C
Light Dimension (mm)	849 (L)×386(H) x108(D)
Solar Panel	18V 65W
PIR	Up to 30metres
Light Weight	10kg
Warranty	5 year

Refresh Lighting & Energy Solutions PTY LTD. 1/13 Commerce Circuit, Yatala QLD 4207 Phone - 1300 911 866 Website - www.refreshlighting.com.au Email – info@refreshlighting.com.au