


- 6. Premium Bridgelux LED chips <100,000 hours
- 7.4 lighting modes
- 8. Adjustable mounting spigot
- 9. Automatic day/night sensor
- 10. User friendly







controlled

| SPECIFICATION         |   |
|-----------------------|---|
| Colour                | 6500K                                   |
| Lumen (Im) – Full     | 10,200lm                                |
| Light Source          | LED                                     |
| Beam Angle            | 140°                                    |
| Mounting Height       | 6-8metres(suggest install 20-27m apart) |
| Power Consumption     | 60W                                     |
| Solar Battery         | 42AH 12.8V                              |
| Charging time         | 6 hours of bright sunlight              |
| Redundancy            | 3 ~ 7 Days                              |
| Housing               | Aluminium + PC                          |
| Operation Temperature | -25°C~+65°C                             |
| Light Dimension (mm)  | 1078 (L)×386(H) x108(D)                 |
| Solar Panel           | 18V 80W                                 |
| PIR                   | Up to 30metres                          |
| Light Weight          | 12.7kg                                  |
| Warranty              | 3 year                                  |

Refresh Lighting & Energy Solutions PTY LTD. 1/13 Commerce Circuit, Yatala QLD 4207 Phone – 1300 911 866 Website – www.refreshlighting.com.au Email – info@refreshlighting.com.au