


- 5. Remote control, UVA technology, 30m control operation
- 6. Premium Bridgelux LED chips <100,000 hours
- 7.4 lighting modes
- 8. Adjustable mounting spigot
- 9. Automatic day/night sensor
- 10. User friendly





SPECIFICATION	
Colour	6500K
Lumen (Im) – Full	10,200lm
Light Source	LED
Beam Angle	140°
Mounting Height	6-8metres(suggest install 20-27m apart)
Power Consumption	60W
Solar Battery	42AH 12.8V
Charging time	6 hours of bright sunlight
Redundancy	3 ~ 7 Days
Housing	Aluminium + PC
Operation Temperature	-25°C~+65°C
Light Dimension (mm)	1078 (L)×386(H) x108(D)
Solar Panel	18V 80W
PIR	Up to 30metres
Light Weight	12.7kg
Warranty	5 year

Specifications are subject to change without notice

Refresh Lighting & Energy Solutions PTY LTD. 1/13 Commerce Circuit, Yatala QLD 4207 Phone - 1300 911 866

Website - www.refreshlighting.com.au Email - info@refreshlighting.com.au

Refresh Lighting solar products are designed for dusk to dawn operation with added allowance for winter conditions, however you must be aware that in winter month it is possible that some nights the light will not last all night due to inclement weather conditions limiting charging time. Solar is not recommended for any locations classed as critical lighting areas where lighting is required all night.