

## LED Slimline Flood Light – 500W

Model: RLFL500W

LED flood lights are suitable for both outdoor and indoor commercial applications such as parking areas, billboards and common areas.

### Product Features

- 90° Beam Angle
- Aluminium die cast housing
- Toughened glass face
- Long operating life and performance
- Weight: 15kg
- IP66 Waterproof housing




Options:




Cut-off Hood

### Lens Options:

Round Beam



Asymmetric Forward Throw



60° Round Beam

Height	Ravg, Rmax	Angle: 56.27deg	Diameter
1m	32727,547741x		106.94cm
2m	8182,136931x		213.89cm
3m	3636,60861x		320.83cm
4m	2045,34231x		427.77cm
5m	1309,21911x		534.72cm
6m	909.1,15211x		641.66cm
7m	667.9,11181x		748.60cm
8m	511.4,855.91x		855.55cm
9m	404.0,676.21x		962.49cm
10m	327.3,547.71x		1069.43cm



### SPECIFICATION

Colour	Cool White (5000K)
Lumen (lm)	59500lm
Efficiency (Lm/w)	>119lm/w
Light Source	LED
CRI (%)	>80%
Beam Angle	60° or 150x80°
Power Requirement	AC 90~305V
Power Consumption	500W
Housing	Die Cast Aluminium and Toughened Glass
Lifespan	> 50,000 hours
Operation Temperature	-20°C~+45°C
Dimension (mm)	672 × 534 × 188mm
Impact Rating	IK08
Protection Rating	IP66
Warranty	5 years